

**V ZONE DESIGN CERTIFICATE**

Name \_\_\_\_\_ Policy Number (Insurance Co. Use) \_\_\_\_\_  
Building Address or Other Description \_\_\_\_\_  
Permit No. \_\_\_\_\_ City \_\_\_\_\_ State \_\_\_\_\_ Zip Code \_\_\_\_\_

**SECTION I: Flood Insurance Rate Map (FIRM) Information**

Community No. \_\_\_\_\_ Panel No. \_\_\_\_\_ Suffix \_\_\_\_\_ FIRM Date \_\_\_\_\_ FIRM Zone(s) \_\_\_\_\_

**Section II: Elevation Information Used for Design**

*[NOTE: This section documents elevations used in the design- it does not substitute for an Elevation Certificate.]*

- 1. FIRM Base Flood Elevation (BFE) ..... \_\_\_\_\_ feet\*
- 2. Community's Design Flood Elevation (DFE) ..... \_\_\_\_\_ feet\*
- 3. Elevation of the Bottom of the Lowest Horizontal Structure Member..... \_\_\_\_\_ feet\*
- 4. Elevation of Lowest Adjacent Grade ..... \_\_\_\_\_ feet\*
- 5. Depth of Anticipated Scour/Erosion used for Foundation Design ..... \_\_\_\_\_ feet\*
- 6. Embedment Depth of Pilings of Foundation Below Lowest Adjacent Grade ..... \_\_\_\_\_ feet\*

\* Indicate elevation datum used in 1-4:  NGVD29  NAVD88  Other \_\_\_\_\_

**SECTION III: V Zone Design Certification Statement**

*[NOTE. This Section must be certified by a registered engineer or architect.]*

I certify that: (1) I have developed or reviewed the structural design, plans, and specifications for construction and (2) that the design and methods of construction to be used are in accordance with accepted standards of practice for meeting the following provisions:

- The bottom of the lowest horizontal structural member of the lowest floor (excluding piles and columns) is elevated at or above the BFE plus 1 foot of freeboard; and
- The pile and column foundation and structure attached thereto is anchored to resist floatation, collapse, and lateral movement due to the effects of the wind and water loads acting simultaneously on all building components. Water loading values used are those associated with the base flood. Wind loading values used are those required by the applicable State of local building code. The potential for scour and erosion at the foundation has been anticipated for conditions associated with the base flood, including wave action.

**SECTION IV: Breakaway Wall Design Certification Statement**

*[NOTE. This section must be certified by a registered engineer or architect when breakaway walls exceed a design safe loading resistance of 20 pounds per square foot.]*

I certify that (1) I have developed or reviewed the structural design, plans and specifications for construction and (2) that the design and methods of construction to be used for the breakaway walls are in accordance with accepted standards of practice for meeting the following provisions:

- Breakaway wall collapse shall result from a water load less than that which would occur during the base flood; and
- The elevated portion of the building and supporting foundation system shall not be subject to collapse, displacement, or other structural damage due to the effects of wind and water loads acting simultaneously on all building components (wind and water loading values to be used are defined in Section III).

**SECTION V: Certification and Seal**

This certification is to be signed and sealed by a registered professional engineer or architect authorized by law to certify structural designs. I certify the V Zone Design Certification Statement (Section III) and \_\_\_\_\_ the Breakaway Wall Design Certification Statement (Section IV, check if applicable).

Certifier's Name \_\_\_\_\_ License Number \_\_\_\_\_  
Title \_\_\_\_\_ Company Name \_\_\_\_\_  
Address \_\_\_\_\_  
City \_\_\_\_\_ State \_\_\_\_\_ Zip Code \_\_\_\_\_

Signature \_\_\_\_\_ Date \_\_\_\_\_ Telephone \_\_\_\_\_

